

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-222474

(43)Date of publication of application : 17.08.2001

(51)Int.Cl.

G06F 13/00  
G06F 3/00  
G06F 13/38  
H03K 19/0175  
H04L 1/00  
H04L 25/02

(21)Application number : 2000-029103

(71)Applicant : INTERNATL BUSINESS MACH  
CORP <IBM>

(22)Date of filing : 07.02.2000

(72)Inventor : OSHIKAWA HIROSHI  
SAKAI TATSUYA  
ASANO HIDEO  
SATO MASAHIKO

(54) SIGNAL OUTPUT DEVICE, DRIVER CIRCUIT, SIGNAL TRANSMISSION SYSTEM, AND METHOD FOR TRANSMITTING SIGNAL

(57)Abstract:

PROBLEM TO BE SOLVED: To realize a high signal integrity at all settable data transfer speeds.

SOLUTION: A signal output device capable of setting up plural different data transfer speeds and outputting a signal to a signal receiver at a certain set data transfer speed via an ATA cable 2 is provided with a driver circuit 53 capable of setting up plural different through rates and outputting the signal to the ATA cable 2 at a through rate set in accordance with a through rate control signal SRC and a control means for setting up the through rate of the driver circuit 53 in accordance with the set data transfer speed.

